

| DECLARATION OF PERFORMANCE |   |
|----------------------------|---|
| Reference :                | DOPFibraluxMRBlackGlossv1                                 |
| Commercial name :          | Fibralux MR Black Gloss                                   |
| Product type :             | MDF Fibreboard with primer coating                        |
| Reference standard :       | Wood Based Panel - EN13986:2004+A1:2015 Annex A Table A.9 |
| CE Class :                 | MDF.HLS   |
| Field of application :     | Internal use as structural component in humid conditions  |
| AVCP Class :               | 2+  |
| Certification number:      | 1161-CPR-0141 [6-30mm]                                    |
| Produced at:               | Rue de la Forêt 2, B-6690 Vielsalm                        |

| Essential Characteristic                                | Unit              | Reference             | Thickness range (mm) |           |           |           |           |        |
|---|-------------------|-----------------------|----------------------|-----------|-----------|-----------|-----------|--------|
|   |                   |                       | 6                    | >6 - 9    | > 9 - 12  | >12-19    | >19-30    | >30-45 |
| Bending strength  | N/mm <sup>2</sup> | EN 622-5              | 34                   | 34        | 32        | 30        | 28        | NPD    |
| Modulus of elasticity in bending                        | N/mm <sup>2</sup> | EN 622-5              | 3000                 | 3000      | 2800      | 2700      | 2600      | NPD    |
| Internal bond   | N/mm <sup>2</sup> | EN 622-5              | 0,70                 | 0,80      | 0,80      | 0,75      | 0,75      | NPD    |
| Swelling in thickness, 24h                              | %                 | EN 622-5              | 18                   | 12        | 10        | 8         | 7         | NPD    |
| Moisture resistance OPTION 1 :<br>Internal bond         | N/mm <sup>2</sup> | EN 622-5              | 0,35                 | 0,3       | 0,25      | 0,2       | 0,15      | NPD    |
| Moisture resistance OPTION 1 :<br>Swelling in thickness | %                 | EN 622-5              | 25                   | 19        | 16        | 15        | 15        | NPD    |
| Surface Soundness                                       | N/mm <sup>2</sup> | EN 622-5              | NPD                  | NPD       | NPD       | NPD       | NPD       | NPD    |
| Formaldehyde class                                      | Class             | EN 13986-table B1     | E1                   | E1        | E1        | E1        | E1        | NPD    |
| Reaction to fire  | Class             | EN 13501-1            | E                    | D-s2d0(*) | D-s2d0    | D-s2d0    | D-s2d0    | NPD    |
| Water vapour permeability $\mu$                         | wet<br>dry        | EN 13986 - table 9    | NPD                  | NPD       | NPD       | NPD       | NPD       | NPD    |
| Airborne sound insulation                               | dB                | EN 13986-5.10         | NPD                  | NPD       | NPD       | NPD       | NPD       | NPD    |
| Sound absorption $\alpha$                               |                   | EN 13986 - table 10   | 0,10/0,20            | 0,10/0,20 | 0,10/0,20 | 0,10/0,20 | 0,10/0,20 | NPD    |
| Thermal conductivity $\lambda$                          | W/m.K             | EN 13986 - table 11   | 0,1                  | 0,1       | 0,1       | 0,1       | 0,1       | NPD    |
| Strength - tension ft                                   | N/mm <sup>2</sup> | EN 12369-1            | 18                   | 18        | 18        | 16,5      | 16        | NPD    |
| Strength - compression fc                               | N/mm <sup>2</sup> | EN 12369-1            | 18                   | 18        | 18        | 16,5      | 16        | NPD    |
| Strength - bending $f_m$                                | N/mm <sup>2</sup> | EN 12369-1            | 22                   | 22        | 22        | 22        | 21        | NPD    |
| Strength - panel shear $f_v$                            | N/mm <sup>2</sup> | EN 12369-1            | 8,5                  | 8,5       | 8,5       | 8,5       | 8,5       | NPD    |
| Strength - planar shear $f_r$                           | N/mm <sup>2</sup> | EN 12369-1            | NPD                  | NPD       | NPD       | NPD       | NPD       | NPD    |
| Stiffness - tension $E_t$                               | N/mm <sup>2</sup> | EN 12369-1            | 3200                 | 3200      | 3200      | 3100      | 2800      | NPD    |
| Stiffness - compression $E_c$                           | N/mm <sup>2</sup> | EN 12369-1            | 2800                 | 2800      | 2800      | 2700      | 2400      | NPD    |
| Stiffness - bending $E_m$                               | N/mm <sup>2</sup> | EN 12369-1            | 2800                 | 2800      | 2800      | 2700      | 2400      | NPD    |
| Stiffness - panel shear $G_v$                           | N/mm <sup>2</sup> | EN 12369-1            | 1000                 | 1000      | 1000      | 1000      | 800       | NPD    |
| Impact resistance                                       | Class             | EN 12871              | NPD                  | NPD       | NPD       | NPD       | NPD       | NPD    |
| Punishing shear strength $R_{mean}$                     | N/mm <sup>2</sup> | EN 1195               | NPD                  | NPD       | NPD       | NPD       | NPD       | NPD    |
| Punishing shear strength $F_{ser,k}$                    | N/mm <sup>2</sup> | EN 1195               | NPD                  | NPD       | NPD       | NPD       | NPD       | NPD    |
| Punishing shear strength $F_{max,k}$                    | N/mm <sup>2</sup> | EN 1195               | NPD                  | NPD       | NPD       | NPD       | NPD       | NPD    |
| Linear expansion $\delta_{30,85}$                       | mm/m              | EN 318                | NPD                  | NPD       | NPD       | NPD       | NPD       | NPD    |
| Mechanical durability<br>(kmod; kdef)                   |                   | Shall be taken from : | NPD                  | NPD       | NPD       | NPD       | NPD       | NPD    |
| Biological durability                                   | Service<br>Class  | EN 335                | 1                    | 1         | 1         | 1         | 1         | NPD    |
| Content of PCP  | ppm               | EN 13986-5.18         | <5                   | <5        | <5        | <5        | <5        | NPD    |

(\*) <9mm : E; 9mm : D-s2,d0

| Informative Characteristic | Unit  | Reference  | Thickness range (mm)                       |        |          |        |        |        |
|----------------------------|-------|------------|--|--------|----------|--------|--------|--------|
|                            |       |            | 6  | >6 - 9 | > 9 - 12 | >12-19 | >19-30 | >30-45 |
| Formaldehyde class         | Class | ASTM E1333 | CARB 2 < 0.11 ppm [6 -> 38mm]              |        |          |        |        |        |
| Formaldehyde class         | Class | ASTM E1333 | TSCA Title VI (EPA) < 0.11 ppm [6 -> 38mm] |        |          |        |        |        |

Version date :  
6/05/2019

Lode De Boe,  
President UNILIN bvba, division panels

