

# Fibrofit<sup>®</sup> Prime

# Ready-to-paint MDF with a lacquer primer

Fibrofit Prime is an MDF board with a well-sealed surface and an even white primer coating on both sides. This environmentally friendly primer coating has high dry matter content and is applied with rollers. Ultraviolet light is used to help harden it, which results in a high-quality primer surface. These boards can be used in service class 1 (dry environments) and can only be used in the biological hazard class 1 of Standard EN-335-3.

## Applications

- Interior decoration
- Furniture production

## Characteristics

D L-MDF (EN 622-5)

Ready to paint





## Fibrofit<sup>®</sup> Prime

### **Applications**

The versatile Fibrofit Prime board is perfectly suited to interior finishes, furniture, stand-building and shop furnishings, but can also be used as a non-load bearing wall or ceiling. What is more, Fibrofit Prime is the ideal solution for every DIY enthusiast who wants to get professional results quickly and easily. The industrially lacquered Fibrofit Prime surface can be painted or lacquered in a final colour of your choice without pre-treatment. Furthermore, Fibrofit Prime guarantees excellent adhesion and a great finish with no wasted paint or swollen MDF fibres.

### **Technical specifications**

General characteristics + Standard	Unit	Average values			
Thickness EN 324-1	mm	9	12	16	18
Technical characteristics + Standard	5/95 percentile values				
Bending strength EN 310	N/mm <sup>2</sup>	20	20	18	18
Bending stiffness EN 310	N/mm <sup>2</sup>	1700	1700	1600	1600
Internal bond EN 319	N/mm <sup>2</sup>	0,45	0,45	0,45	0,45
Swelling/24h EN 317	%	20	16	14	14

Fibrofit Prime comes under formaldehyde emission class E1 and meets the general requirements as described in Table 1 of EN Standard 622-1

### Available dimensions and thicknesses

Fibrofit Prime is available from stock in various thicknesses and sizes. Consult the complete UNILIN Panels stock range at www.unilinpanels.com. For our technical capabilities on custom thicknesses and dimensions, as well as minimum order requirements, please contact our sales team or email info.panels@unilin.com.

### Certificates

UNILIN Division Panels is actively committed to sustainable forest management. Fibrofit Prime is available on demand with PEFC and FSC labelling.





UNILIN, division panels **Solution** Ingelmunstersteenweg 229 - 8780 Oostrozebeke - Belgium info.panels@unilin.com / www.unilinpanels.com